



# Lifeline® MC: One-Hour and Two-Hour Fire Resistive Multiconductor Cables – UL 2196

Fire Resistive Cable for Survivability in a Fire



## Applications

Lifeline® MC fire resistive cables were designed to meet and have successfully passed one-hour and two-hour fire rating certification tests per UL 2196, *Standard for Tests for Fire Resistive Cables*.

**Lifeline® MC Cables can be used in the following applications to provide survivability during a fire:**

- Tall Buildings
- Emergency Feeder Cables
- Stairwell Pressurization
- Elevators / OEO
- Emergency lighting for roadway and transit tunnels when cables include optional LSZH jacket over armor
- Fire Pumps
- Ventilating Fans
- Exit Lighting

Lifeline® MC Cables are preferred over Mineral Insulated (MI) cables, concrete encasement or the construction of fire rated assemblies based on the facts that Lifeline® MC Cables are less costly and easier to install for many applications.

Fire resistive cables are required per NFPA 70/NEC, Articles 517, 695, 700, 708, 728 and 760 as well as NFPA 72 and NFPA 101.

## Specifications and Ratings

- Listed to UL 1569, Metal Clad Cables, as the following type:
- Type MC 600 Volt, Rated 90°C
- For Cable Tray Use IEEE 1202/ FT4 Rated, ST1 Limited Smoke
- Classified to UL 2196, Standard for Tests for Fire Resistive Cables, with one-hour and two-hour Fire Resistive Rating (FRR)
- Electrical Circuit Integrity System (FHIT) No. 50 of the UL Fire Resistance Directory with 2-hour FRR at 480 volts utilization covers cable constructions in table below and optional taped splice for conductor sizes 2AWG and larger.
- Electrical Circuit Integrity System (FHIT) No. 50A of the UL Fire Resistance Directory with 1-hour FRR at 480 volts utilization, covers multi-conductor cable constructions 4 conductor 2AWG with segmented ground conductors and 3 conductor 14 AWG, and optional ceramic stand-off splice for conductor sizes 14AWG to 350MCM.
- Optional taped splice in Electrical Circuit Integrity System (FHIT) No. 50 of the UL Fire Resistance Directory with 2-hour FRR at 480 volts utilization.
- Optional ceramic stand-off splice for conductor sizes up to 350MCM in Electrical Circuit Integrity System (FHIT) No. 50A of the UL Fire Resistance Directory with 1-hour FRR at 480 volts utilization.
- NFPA 70, NFPA 101 compliant
- Corrugated Copper Armor meets Equipment Grounding Conductor requirements of NEC Table 250.122

## Design Parameters

**CONDUCTORS:** Bare stranded copper, 14 AWG through 600 kcmil

**INSULATION:** Ceramifiable Silicone Zero Halogen (LSZH)

**INNER BINDER JACKET:** Ceramifiable Silicone Zero Halogen (LSZH)

**ARMOR:** Continuously Welded and Corrugated Copper

### IDENTIFICATION:

DRAKA MA P/N [#####] [X]/C [Y] LIFELINE (UL) E66840T MC-ST1 600V 90C FOR CT USE IEEE 1202/FT4 ST1 (UL) R19359 FRR 2HR FHIT#50<sup>1</sup> or FRR 1HR FHIT#50A<sup>2</sup> UL 2196 480V UTILIZATION (MONTH/YEAR) (SEQUENTIAL FOOTAGE) Notes: [#] is cable part number

[X] is the number of conductors

[Y] is cable size in AWG or kcmil

<sup>1</sup> FRR 2HR FHIT#50 includes taped splice for cables with conductor sizes 2AWG to 600MCM

<sup>2</sup> FRR 1HR FHIT#50A applies ceramic stand-off splice for cables with 14AWG to 350MCM conductors



**RoHS**  
COMPLIANT



# Lifeline® MC: One-Hour and Two-Hour Fire Resistive Multiconductor Cables – UL 2196

Fire Resistive Cable for Survivability in a Fire

## Lifeline® MC Power Cable

LIFELINE® Part Number	Conductor Size AWG /MCM	Number of Cond	Nominal Core Diameter (in)	Nominal Armor Diameter (in)	Ampacity* 75°C Amps	Ampacity* 90°C Amps
LMC05014	14	5	0.66	0.97	20**	25**
LMC02012	12	2	0.56	0.85	25**	30**
LMC03012	12	3	0.59	0.91	25**	30**
LMC04012	12	4	0.64	0.97	25**	30**
LMC05012	12	5	0.70	0.97	25**	30**
LMC02010	10	2	0.61	0.85	35**	40**
LMC03010	10	3	0.64	0.97	35**	40**
LMC04010	10	4	0.70	0.97	35**	40**
LMC05010	10	5	0.77	1.08	35**	40**
LMC02008	8	2	0.70	0.97	50	55
LMC03008	8	3	0.75	1.08	50	55
LMC04008	8	4	0.82	1.18	50	55
LMC05008	8	5	0.90	1.26	50	55
LMC02006	6	2	0.78	1.08	65	75
LMC03006	6	3	0.83	1.18	65	75
LMC04006	6	4	0.91	1.26	65	75
LMC05006	6	5	1.00	1.35	65	75
LMC03004	4	3	0.95	1.35	85	95
LMC04004	4	4	1.04	1.35	85	95
LMC05004	4	5	1.15	1.58	85	95
LMC03003	3	3	1.00	1.35	100	115
LMC04003	3	4	1.11	1.40	100	115
LMC03002	2	3	1.07	1.40	115	130
LMC04002	2	4	1.18	1.58	115	130
LMC03001	1	3	1.24	1.73	130	145
LMC04001	1	4	1.37	1.73	130	145
LMC031/0	1/0	3	1.33	1.73	150	170
LMC041/0	1/0	4	1.47	1.85	150	170
LMC032/0	2/0	3	1.41	1.85	175	195
LMC042/0	2/0	4	1.56	1.97	175	195
LMC033/0	3/0	3	1.52	1.97	200	225
LMC043/0	3/0	4	1.69	2.15	200	225
LMC034/0	4/0	3	1.64	2.15	230	260
LMC044/0	4/0	4	1.82	2.28	230	260
LMC03250	250	3	1.81	2.28	255	290
LMC04250	250	4	2.00	2.52	255	290
LMC03350	350	3	2.04	2.52	310	350
LMC04350	350	4	2.26	2.72	310	350
LMC03400	400	3	2.13	2.72	335	380
LMC04400	400	4	2.37	2.83	335	380
LMC03500	500	3	2.31	2.83	380	430
LMC04500	500	4	2.57	3.11	380	430
LMC03600	600	3	2.54	3.11	420	475
LMC04600	600	4	2.83	3.41	420	475

\*Ampacities are based on Table 310.15(B)(16) of the National Electrical Code (NEC) (NFPA 70-2017) for 3 current carrying conductors at 30°C ambient.

\*\*Small overcurrent protection limitations per NEC Article 240.4(D): (3) 14AWG – 15amps, (5) 12AWG – 20amps, (7) 10AWG – 30amps

The above dimensions are approximate and subject to normal manufacturing tolerances. Information subject to change

© DRAKA - A Brand of The Prysmian Group. 2020 All Rights Reserved. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed correct at the time of issue. Prysmian Group reserves the right to amend any specifications without notice. These specifications are not contractually valid unless authorized by Prysmian Group. Issued August 2020.